







STAND ALONE SAFETY SWITCHES (No Safety Relay Needed)



Ref	Options	Safety Category		Contacts	Wiring	Housing	Features	
		Alone	On saf. relay					
VIGIL	SXR	3 PLe	3	2NO + 1NC	cable	polycarbonate	Automatic restarting	
	SXRS	4 PLe	4				Manual restarting Auto-control integrated	
AMX3 	AMX3	3 PLe	only with single channel safety modules	1NO + 1NC	cable	polycarbonate	Switching distance 10mm Misalignment 7mm 2A/48V safety lines in-house LED Auto-control integrated	
	AMX3-OX							st. steel
	AMX3-OX-MKT							st. steel
	AMX3-MKT							polycarbonate
AMX4	AMX4	3 PLe		2NO	cable	polycarbonate		
AMX5	AMX5							4
	AMX5-OX	st. steel						
	AMX5-OX-MKT	st. steel						
	AMX5-MKT	polycarbonate						
	AMX5-CM12			Embedded M12	polycarbonate			
AMX R	AMXR	3 PLd	4	2NO + 1NC	cable	PA 6	RFID Switching 20mm/Misag. 15mm Special oil-resistant cable and housing Auto-control integrated	
AMX5 CK 	AMX5 CK	3	4	2NO + 1NC	Embedded M12	polycarbonate	Captive key system Anti-locking: impossibility to restart the machine without locked key in the switch Auto-control integrated	
BOSTER 	BOSTER	3 PLe	4	2NO + 1NC	cable	st. steel	Permanent magnetic latch 4 KG Laser writing 2A/48V safety lines Side or front fixing holes Auto-control integrated	
MASSIMOTTO 	X5 M12 AR	3 PLe	4	2NO + 1NC	Embedded M12 (double connector in option)	polycarbonate	With monitored restarting option double emitter option double connector (X5.2) Auto-control integrated	
	X5 M12 SR						Without monitored restarting option double emitter option double connector (X5.2) Auto-control integrated	
3SSR	3SSR	1 PLC	3 (4 with one switch)	1NO + 1NC	cable	polycarbonate	Switching distance 10mm Misalignment 10mm 2A/250V safety lines	
4SSR	4SSR			2NO	cable	polycarbonate		
5SSR	5SSR			2NO + 1NC		cable	polycarbonate	Switching distance 10mm Misalignment 10mm 2A/250V safety lines version BXUS: 1 LED bicolor version BX : 1 LED monocolor
	5SSR-MKT	M12 pigtail						
	5SSR-OX	st. steel						
	5SSR-OX-MKT	M12 pigtail	st. steel					
OPTO 2s	OPTO 2S	1 PLC	3 (4 with one switch)	2 NO	cable	polycarbonate	Switch. dist 7mm misalign. 3mm 250mA/48V safety lines special for small access	